

230-2010 旋入式塞頭 Nylon Screw Plugs


公制 (Metric)

PG

G (PF)

RoHS Compliant

防水等級：機板平整條件下 未裝墊片 IP65 加裝墊片 IP68



螺牙規格 Thread	規格 Sizes	編號 Cat. No.			尺寸 Dimensions		包裝 Std. Pkg. pcs	
		黑 RAL 9005	淺灰 RAL 7035	銀灰 RAL 7001	A mm	B mm		
M12 X 1.5	SPG - M12	B	G	SG	6.5	16	100	
M16 X 1.5	SPG - M16	B	G	SG	8	20	100	
M20 X 1.5	SPG - M20	B	G	SG	8	25	100	
M25 X 1.5	SPG - M25	B	G	SG	8.5	30	100	
M32 X 1.5	SPG - M32	B	G	SG	10	38	50	
M40 X 1.5	SPG - M40	B	G	SG	13	47	50	
M50 X 1.5	SPG - M50	B	G	SG	14	57	10	
M63 X 1.5	SPG - M63	B	G	SG	15	70	10	
PG 7	SPG - PG7	B	G	SG	6.5	16	100	
PG 9	SPG - PG9	B	G	SG	6.5	19	100	
PG 11	SPG - PG11	B	G	SG	6.5	22.5	100	
PG 13.5	SPG - PG13.5	B	G	SG	7	25.2	100	
PG 16	SPG - PG16	B	G	SG	8	27.5	100	
PG 21	SPG - PG21	B	G	SG	9	34	100	
PG 29	SPG - PG29	B	G	SG	8.5	44.6	50	
PG 36	SPG - PG36	B	G	SG	11	55	50	
G (PF)	1/4	SPG - PF13	B	G	SG	6.5	17	100
	3/8	SPG - PF17	B	G	SG	8	20.5	100
	1/2	SPG - PF21	B	G	SG	8	26	100
	3/4	SPG - PF26	B	G	SG	10	32	100
	1	SPG - PF33	B	G	SG	12	40	50
	1 1/4	SPG - PF42	B	G	SG	13	49	50

- 產品材質：採用 UL 認可之尼龍 PA66 製成（防火等級 UL 94V-2）。
- 顏色種類：黑色及灰色。
- 使用方法：1. 對應設備適合之公制牙（Metric）、G（PF）牙及 PG 牙孔使用，以螺絲起子旋緊即可。
2. 對應設備適合之開孔口徑，搭配尼龍固定螺帽（請見目錄第 230-3010 類）以及防水橡膠墊片（請見目錄第 230-4010 類），一起固定在開孔上。
- 產品用途：作為預留孔塞平之用。

